




Sensing Solutions since 1959

M3326 Series Technical Data Sheet

Subminiature Float Switch



M3326



Applications

- Detects high/low levels in a container
- Polypropylene holds up well in acidic or alkaline liquids
- FDA approved for food contact
- Can be used in low temperature food equipment applications (up to 221°F, 105°C) such as food service steamers and proofers

Custom Solutions

At times, OEMs, end users or military specifiers require a customized solution or sample product to test. Madison Company can design, manufacture and ship a custom switch or sensor in just six business days. Simply communicate the quantity and requirements to our technical sales staff. We will quote the product to establish budget and ROI. Following the quote approval, Madison engineers will design the switch or sensor that satisfies the application specifications, and provide proof of concept. Upon approval, we will build and ship the product or sample.

Related Products



M3326-NO



M3326-NPT



M3326-NPT-NO

View in-stock products ready to ship today at Madisonco.com/buy

Madison Company, Inc.
27 Business Park Drive
Branford, CT 06405

203-488-4477 or 800-466-5383
info@madisonco.com
www.madisonco.com



M3326 Series Technical Data Sheet

Subminiature Float Switch

Single Point, Vertically-Mounted Switch Specifications

Normally Closed unless otherwise indicated

* Indicates sensor in stock for same day shipment.

Model	Approvals	Float/Stem Material	Float Specific Gravity (SG)	Lead Wires	Max. Pressure	Max. Temp.	Mounting	Slosh Shield	Switch Rating	Electrical Ratings
M3326*	CE, UL, NSF	Polypropylene/ Polypropylene	0.6	24", 24 AWG, Teflon Insulated	50 PSI	221°F (105°C)	3/8-16 UNC	No	15 Watt, SPST	120 VAC, 0.12A; 100 VDC, 0.10A; 24 VDC, 0.30A; 12 VDC, 0.30A
M3326-NO* (Normally Open)	CE, UL, NSF	Polypropylene/ Polypropylene	0.6	24", 24 AWG, Teflon Insulated	50 PSI	221°F (105°C)	3/8-16 UNC	No	15 Watt, SPST	120 VAC, 0.12A; 100 VDC, 0.10A; 24 VDC, 0.30A; 12 VDC, 0.30A
M3326-NPT	CE	Polypropylene/ Polypropylene	0.6	24", 24 AWG, Teflon Insulated	50 PSI	221°F (105°C)	1/8" NPT	No	15 Watt, SPST	120 VAC, 0.12A; 100 VDC, 0.10A; 24 VDC, 0.30A; 12 VDC, 0.30A
M3326-NPT-NO (Normally Open)	CE	Polypropylene/ Polypropylene	0.6	24", 24 AWG, Teflon Insulated	50 PSI	221°F (105°C)	1/8" NPT	No	15 Watt, SPST	120 VAC, 0.12A; 100 VDC, 0.10A; 24 VDC, 0.30A; 12 VDC, 0.30A

Note: Switches are rated for resistive loads. To see our electrical considerations for UL guidelines for current (Amperes resistive) at different voltages, please visit: <https://madisonco.com/electrical-considerations>

M3326 Series Technical Data Sheet

Subminiature Float Switch

General Information

1. Switches should be installed rigidly so the float or floats are free to move as the liquid level changes.
2. Switches should be mounted in a tank area free of severe turbulence or protected from such turbulence by appropriate and adequate slosh shields.
3. Vertical switch stems should be vertical for best results, but satisfactory operation is possible in most liquids with the stem at up to a 30° angle from vertical.
4. Side mount switch stems must be mounted with the arrow vertically either up or down depending on switch operation.
5. Care should be taken that switches are always operated within electrical ratings.
6. Orientation for standard Vertical switches can be changed from normally open to normally closed dry or vice versa by removing the float and reversing it in the stem, except with the M3326.

Maintenance

Maintenance should consist of inspection to see that the float is free to move and not coated with any substance, which would change its weight or volume significantly. If this occurs, the float should be cleaned. This is easily accomplished without disturbing the installation. In addition, the stem may be wiped down to remove any build-up.

The only repair possible in the field is replacement of either the float or stem. Dents or nicks on the float are usually of no consequence to operation.

Cautions

1. The pressure, temperature and electrical limitations shown for the specified level switches must not be exceeded.
2. The pressures and temperatures must take into consideration possible surges in the temperature and pressure of the system.
3. The liquids used must be compatible with the materials of construction. Specifications of materials will be given upon request.
4. Life expectancy of the switch varies with applications. Contact the factory if life cycle testing is required.
5. Ambient temperature changes can affect switch set points, since specific gravities of liquids vary with temperature. Consult factory for assistance.
6. Level switches have been designed to be shock and vibration resistant. For maximum life, both shock and vibration should be minimized. Consult factory for assistance.
7. Excessive contaminants in fluid may inhibit float operation, and occasional wipe down may be necessary.
8. Level switches must not be field repaired
9. Physical damage to product may render product unserviceable.
10. Installation in a vessel made from magnetic materials may affect operation.

View in-stock products ready to ship today at Madisonco.com/buy



Madison Company, Inc.
27 Business Park Drive
Branford, CT 06405

203-488-4477 or 800-466-5383
info@madisonco.com
www.madisonco.com

